

**DS-KS6150
SIP Server**

- Embedded operating system SIP server
- Up to 50 linked SIP extension, 25 concurrent calls
- Dual 10/100/1000 Mbps network ports
- FXS/FXO/BRI ports supported (optional expansion modules are required)
- GSM/3G/4G modules supported (optional)



▪ Specification

System parameters	
ROM	8GB
RAM	2GB
Processor	1.8GHz ARM Cortex
Video parameters	
Video codecs	VP8, H263, H263P, H264, MPEG4
Audio parameters	
Audio codecs	G711 (alaw/ulaw), G722, G726, G729A, GSM, Speex, ADPCM, iLBC
Capacity	
Base Users / Max Users	50
Max Concurrent Calls	25
Max FXS Ports	8 RJ11 ports
Max FXO/BRI Ports	8 RJ11 ports
Max GSM/3G/4G Ports	4
Max E1/T1/J1 Ports	Not supported
Linked SIP extension	50
Network parameters	
Network protocol	UDP, TCP, TLS, SRTP
DTMF	In-band, RFC4733, RFC2833, SIP INFO
Device interfaces	
Network interface	1xLAN(10/100/1000 Mbps) 1xWAN (10/100/1000 Mbps)
USB	USB2.0
Power supply input	AC 100-240V 50/60HZ 0.6A max
Hard Disk	Not supported
SD card	Not supported
RJ11 port	8 (Max 8 FXS Ports or 8 FXO/BRI Ports)
General	
Weight	1.48KG
Working temperature	0 °C to 40 °C (32 °F to 104 °F)
Storage temperature	-20°C to 65°C (-4°F to 149°F)
Working humidity	10% to 90% (no-condensing)
Dimension (W × H × D)	340 mm × 210 mm × 44 mm (13.39" × 8.27" × 1.74")
Power consumption	≤ 3.3 W

▪ Available Model

DS-KS6150

▪ Dimension



See Far, Go Further



www.hikvision.com
support@hikvision.com

